

OG GREASE 500

LUBRICANT FOR WIRE ROPES

OG GREASE 500 is a solvent-diluting lubricant for open gears and wire ropes. It can be applied by brushing because tacky lubricant is diluted with a solvent providing high permeability, and creates a strong coating after the solvent has evaporated.

● SPECIAL FEATURES

1. Easy to apply

OG GREASE 500 can be applied by brushing without heating because tacky lubricant is diluted with a solvent.

2. Excellent load-carrying and anti-wear properties

OG GREASE 500 is highly resistant to shock load because of its extraordinary strong tacky film after the solvent has evaporated. It prevents wear by protecting friction components.

3. Excellent rust and corrosion preventive properties

OG GREASE 500 is not easily washed off when sprayed with water. Therefore, gears and wire ropes are ensured extended life because it prevents rust formation and surface corrosion.

● APPLICATIONS

OG GREASE 500 is recommended for use in open gears and wire ropes.

● CONTAINER

16-kg can

● TYPICAL PROPERTIES OF OG GREASE 500

Appearance, Color		Semi Liquid, Black
Viscosity(50°C)	mm ² /s	470
Flash Point (Setaflash Closed Cup Test)	°C	65
Copper Corrosion (Room Temp., 24h)		1

Note: The typical properties may be changed without notice.
(July 2017)



Handling Precautions

▼ Follow these precautions when handling this product.

Composition :	Base Oil, Hydrocarbons(<2%aromatics), Additives
Precautionary pictograms:	
Signal word:	Warning
Hazard Statement:	Combustible liquid May cause respiratory irritation, or May cause drowsiness or dizziness. May cause damage to organs (liver) through prolonged or repeated exposure. Harmful to aquatic life Harmful to aquatic life with long lasting effects.
Precautionary Statements: Prevention	<ul style="list-style-type: none">• Do not handle until all safety precautions have been read and understood. (P202)• Wear protective gloves/protective clothing/eye protection/face protection. (P280)• Do not allow the eyes to become exposed to the product. Do not swallow the product.• Keep away from heat/sparks/open flames/hot surfaces – No smoking. (P210)• Use explosion-proof electrical/ventilating/lighting/equipment. (P241)• Avoid release to the environment. (P273)• Ground/bond container and receiving equipment. (P240)• Use only outdoors or in a well-ventilated area. (P271)• Do not breathe dust/fume/gas/mist/vapours/spray. (P260)• Wash hands thoroughly after handling.• Do not eat, drink or smoke when using this product. (P270)
Response	<ul style="list-style-type: none">• IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. (P301+P310)• IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. (P301+P330+P331)• If the eyes are exposed to the product: Rinse the eyes with plenty of running water and immediately contact a physician.• IF ON SKIN: Wash with plenty of soap and water. (P302+P352)• IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. (P304+P340)• Get medical advice/attention if you feel unwell. (P314)• In case of fire: Use ... for extinction (P370+P378)
Storage	<ul style="list-style-type: none">• The product must be stored in a cool, well-ventilated location where it will not be exposed to direct sunlight.• Containers that have been opened must be tightly sealed.• Store in a well-ventilated place. Keep container tightly closed. (P403+P233)• Store in a well-ventilated place. Keep cool. (P403+P235)• Store locked up. (P405)
Disposal	<ul style="list-style-type: none">• Dispose of contents/container in accordance with local/regional/national/international regulations.• If there are any doubts about proper methods of handling the product, contact the point of purchase before proceeding with usage.